IS7025si

The IS7025si is a popular slim-line, door frame perimeter seal, designed to be fitted to an existing door stop, around the head and jambs of single swing doors.

The aluminium carrier has fixing holes pre-drilled and slotted to allow the seals to be adjusted and positioned accurately. A decorative cover strip is supplied to conceal these fixings.

Gap size

• Min. Omm / max. 6mm

Door set standard lengths

- Single: 1 x 1000mm, 2 x 2100mm
- Long Single: 1 x 1000mm, 2 x 2750mm
- Double:
- Long Double: 1 x 2100mm, 2 x 2750mm

3 x 2100mm

Standard lengths

- 1000mm
- 2250mm
- Also available in: 250mm increments from 1000mm to 5000mm

Standard colours

- Silver anodised aluminium with grey silicone gasket and grey cover strip
- Black anodised aluminium with black silicone gasket and black cover strip

Approval/s

- Fire tested to AS1530 Part 4 in accordance with AS1905 Part 1
- 🕒 Certifications GVYI.R26629, GVWZ.R26629, GVWZ7.R26629
- Acoustically tested in accordance with AS1191, IS0140.3 & IS010140-2



7.5 26

IS7025si



Kilargo IS7025si | Last edit 10/04/2018



Preferred Distributor

Contact Us

- Unit 5 16-18 Riverland Drive Loganholme 4129 (By Appointment Only)
- § 07 3287 7647
- 🖻 info@soundproofwarehouse.com.au
- 🕓 Open 7 Days 9am 5pm